



POWEROIL SAPPHIRE H18

(MILD EXTRACTED SOLVATE - LOW PCA OIL)

POWEROIL SAPPHIRE H 18 is Medium viscosity rubber processing oil, it meets European Regulation (EU directive 2005/69/EC) for Non toxic and Non Carcinogenic Oils of < 3 % PCA Content as per IP: 346 Standard and are PAH free. It is also compatible for processing NR, SBR, PBR, EPDM and Reclaim Rubber.

Sr.No.	Characteristics	Unit	Test Method	Typical Data
1.	Appearance	-	Visual	Clear & Bright
2.	Kin. Viscosity , cSt @ 40°C	cSt	D - 445	150 to 200
3.	Kin. Viscosity , cSt @ 100°C	cSt	D - 445	13.0 to 17.0
4.	Density @ 15°C , gmc/cc	gm/ml	D - 1298	0.895 - 0.925
5.	Density @ 29.5°C , gmc/cc	gm/ml	D - 1298	0.908
6.	Colour ,	-	D - 1500	< 3.0
7.	Flash Point (COC) , °C	°C	D - 92	230
8.	Pour Point , °C	°C	D - 97	-12
9.	Aniline Point, °C	°C	D - 611	85 to 100
10.	Polycyclic Aromatic compounds,	% wt.	IP 346	< 3.0
11.	Poly Aromatic Hydrocarbons (PAH'S), sum of 8 PAH	PPM	EPA - 8082	< 10 PPM

Application:-

- Manufacturing of Tyres, Manufacturing of Automotive Tubes, Retreads, Reclaim Rubber
- Extrusion Profiles, Molded / Extruded Products

(Version # 0, January , 2015)

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.