



## POWEROIL® SAPPHIRE MW H1500

**POWEROIL® SAPPHIRE MW H1500** is processing oil formulated from carefully selected hydrogenated Naphthenic base oils. These Naphthenic oils are more polar in nature than Paraffinic oils and hence they have greater affinity to metal, good cooling properties and excellent low temperature properties.

Sr.No.	Characteristics	Unit	Test Method	Typical Data	
				Min.	Max.
1.	Appearance	-	Visual	Clear Liquid	
2.	Colour, ASTM	-	ASTM D-1500	-	4.0
3.	Density at 29.5°C	gms / ml	ASTM D-1298	0.900	0.930
4.	Kinematic viscosity at 40°C	cSt	ASTM D-445	300	330
5.	Flash Point , ( COC )	° C	ASTM D-92	230	-
6.	Pour Point	° C	ASTM D-97	-	- 9
7.	Aniline Point	° C	ASTM D-611	90	100
8.	Hydrocarbon Type Analysis,		ASTM D-2140		
	C <sub>A</sub>	%		15.0 (Typ.)	
	C <sub>P</sub>	%		30.0(Typ.)	
	C <sub>N</sub>	%		55.0(Typ.)	
9.	Copper Corrosion	-	ASTM D-130	-	1
10.	PCA Content	% Wt.	IP-346	-	3.0

( Version # 0, January ` 2013 )

*Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.*