



POWEROIL FLEXOIL A SUPER

(AROMATIC RUBBER PROCESS OIL)

POWEROIL FLEXOIL A SUPER is an aromatic type rubber processing oil conforming to ASTM 101 Type, formulated from specially selected aromatic extracts. It has good compatibility and suitable for use in NR, SBR, PBR, NBR, CR.Rubbers.

Sr No	Characteristics	Unit	Test Method	Guaranteed Data	
				Min	Max
1	Color		ASTM D - 1500	8.0 (Typical) (Dark Brownish Black)	
2	Density at 29.5° C	gm / ml	ASTM D - 1298	1.0 (Typical)	
3	Kinematic viscosity at 100° C	cSt	ASTM D - 445	18	28
4	Flash Point, COC	° C	ASTM D - 92	220	
5	Pour Point	° C	ASTM D - 97		+30
6	Aniline Point	° C	ASTM D - 611	25	50
7	Viscosity Gravity Constant		ASTM D - 2501	0.93	0.98

APPLICATIONS: POWEROIL FLEX OIL A SUPER is suitable for the following applications :

- Manufacturing of Automotive Tyre & Tube
- Tyre retreading
- Belting & Hoses
- Battery Containers
- All NR extruded products

(Version # 4 December 25th 2012)

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.