



POWEROIL OPAL L 65 (PARAFFINIC RUBBER PROCESS OIL)

POWEROIL OPAL L 65 is low viscosity rubber processing oil conforming to ASTM 104 type, formulated from carefully selected hydrogenated paraffinic base oils. This oil is non staining in nature and posses excellent thermal, oxidation & color stability. It is compatible for processing NR, SBR, PBR rubbers.

Sr. No.	Characteristics	Unit	Test Method	Typical Data	
				Min	Max
1.	Appearance	-	Visual	Clear Liquid	
2.	Colour, ASTM	-	ASTM D-1500	-	3.0
3.	Density at 29.5°C	gms / ml	ASTM D-1298	0.85	0.90
4.	Kinematic viscosity at 40°C	cSt	ASTM D-445	9	14
5.	Flash Point , (COC)	° C	ASTM D-92	150	
6.	Pour Point	° C	ASTM D-97		-12
7.	Aniline Point	° C	ASTM D-611	75	85
8.	Carbon Type Analysis		IR Method		
	Ca (Aromatic Carbon)	%		15 (Typical)	
	Cp (Paraffinic Carbon)	%		55 (Typical)	
	Cn (Naphthenic Carbon)	%		30 (Typical)	

APPLICATIONS : POWEROIL OPAL L 65 is suitable for the following applications :

- Manufacturing of Automotive Tubes
- Light coloured non black Foot Wear products, Molded products.

(Version # 0 June 2015)

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.