

**POWEROIL® PEARL H 500**

Meets the requirements of US FDA 21 CFR 172.878 & 21 CFR 178.3620(a) ,
USP 36 NF 31 (United States Pharmacopoeia).

No.	Characteristics	Unit	Test Method	Typical Data	
				Min.	Max.
1.	Descriptions	-	Visual	A colourless, transparent, oily liquid, free from florescence in day light.	
2.	Color, Saybolt	-	ASTM D 156	+ 30	-
3.	Kinematic Viscosity at 40 °C	cSt	ASTM D 445/ D 7042	90	110
4.	Flash Point, (COC)	° C	ASTM D 92	220	-
5.	Pour Point	° C	ASTM D 97	-	-9
6.	Specific Gravity @ 25 °C	gm/ml	USP	0.845	0.905
7.	Acidity	-	USP	Not more than 1 ml of 0.01 N NaOH	
8.	Readily Carbonisable Substances		USP	Pass	
9.	Polycyclic Aromatic Hydrocarbons	-	USP	Pass	
10.	Solid Paraffin	-	USP	Pass	
11.	Sulfur Compounds	-	USP	Pass	

POWEROIL® PEARL H 500 (Mineral Oil - USP) is a high purity USP grade white mineral oil formulated from highly refined hydrotreated low pour point base oils meeting the extreme purity requirements of the United States Pharmacopoeia which ensures the absence of any significant sulfur, nitrogen, oxygen and halogen derivatives or unsaturated substances and aromatics.

Application : **POWEROIL PEARL H 500** (Mineral Oil - USP) is used in infinite number of applications which includes medical formulations , ointments , laxatives , repository vaccines , hair oils , hair creams , cosmetics , facial creams and lotions , gelatin capsules , protective coatings for fruits and vegetables , veterinary preparations , egg preservatives etc.

(Version # 1, October, 2014)

Apar Industries Ltd., Apar House, Corporate Park, Sion-Trombay Road, Chembur, Mumbai – 400 071.

Product Data Sheet

Tel: 91-22-2526 3400 / 6780 0400 | Fax: 91-22-2524 6326 | website: www.apar.com