



POWEROIL® PEARL M 150



Meets the requirements of following Specifications :

- USP 40/NF 35 (US Pharmacopoeia/National Formulary), Light Mineral Oil.
- US FDA 21 CFR 172.878 & 21 CFR 178.3620(a), White Mineral Oil.

Nonfood Compounds
Program Listed 3H,H-1,HX-1
Registration # 154121

No.	Characteristics	Unit	Test Method	Typical Data	
				Min.	Max.
1.	Descriptions	-	Visual	Colorless, transparent oily liquid, free from florescence in day light.	
2.	Color, Saybolt	-	ASTM D 156	+30	-
3.	Kinematic Viscosity at 40°C	cSt	ASTM D 445/ D 7042	28.8	33.5
4.	Flash Point, (COC)	° C	ASTM D 92	180	-
5.	Pour Point	° C	ASTM D 97	-	-12
6.	Specific Gravity @ 25°C	-	USP	0.818	0.880
7.	Acidity	-	USP	Not more than 1 ml of 0.01 N NaOH	
8.	Readily Carbonisable Substances	-	USP	Pass	
9.	Polycyclic Aromatic Hydrocarbons	-	USP	Pass	
10.	Solid Paraffin	-	USP	Pass	
11.	Sulfur Compounds	-	USP	Pass	

POWEROIL® PEARL M 150 (Light Mineral Oil - USP) is a high purity USP grade white mineral oil formulated from highly refined hydrotreated low pour point base oils meeting the extreme purity requirements of the United States Pharmacopoeia which ensures the absence of any significant sulfur, nitrogen, oxygen and halogen derivatives or unsaturated substances and aromatics.

Application: Used in infinite number of applications which includes medical formulations , ointments , laxatives , repository vaccines , hair oils , hair creams , cosmetics , facial creams and lotions , gelatin capsules, protective coatings for fruits and vegetables, veterinary preparations, egg preservatives etc.

(Version # 2, January, 2018)

Disclaimer: APAR makes no warrantees, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.

