

## BLAZE 4T SYNTH 10W 30

BLAZE 4T SYNTH is a technologically advanced Synthetic 4-stroke motorcycle engine oil formulated with special additives to protect engine, clutch and gears under high RPM and heat. It has super strong film to withstand high load and stressful stop-start city driving and accelerated highway driving conditions. It provides smooth clutch engagement and gear shifting thus minimizing the power loss.

### Advantages:-

- Superior performance and smooth ride by active prevention of friction.
- Superior protection of gears during frequent gear changes.
- Prevention of clutch slippage at start up and at varying speeds.

Recommended for all 4 Stroke Two wheelers manufactured by Hero Moto Corp, Bajaj Auto, TVS, Yamaha, KTM, Suzuki, Mahindra 2 Wheelers, LML, Honda, Aprilia, Enfield etc. and all imported bikes and engines fitted with catalytic converters.

### Typical Characteristics:-

| Sr No | Characteristics       | Unit     | Test Method | Specifications |
|-------|-----------------------|----------|-------------|----------------|
| 1     | Appearance            | -        | Visual      | Clear Liquid   |
| 2     | Color                 | -        | ASTM D-1500 | < 2.5          |
| 3     | Density @29.5°C.      | gm/cc    | ASTM D 1298 | 0.845          |
| 4     | Kin. Viscosity @40°C  | cst      | ASTM D 445  | 70.35          |
| 5     | Kin. Viscosity @100°C | cst      | ASTM D 445  | 10.88          |
| 6     | Viscosity Index       | -        | ASTM D 2270 | 145            |
| 7     | Flash Point           | °C       | ASTM D 92   | 7.63           |
| 8     | Pour Point            | °C       | ASTM D 97   | 232            |
| 9     | TBN                   | mgKOH/gm | ASTM D2896  | -27            |
| 10    | CCS @-25°C            | cp       | ASTM 5293   | 6059           |

### Product Performance Claims:-

Exceeds the requirements of JASO MA2 standards & Valve Train Wear and High Temperature Performance characteristic of API SN.