

Safety Data Sheet Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1	Product Identifier Product name Product description Product type	POWEROIL BLAZE 4T SYNTH (SAE 10W 30) Engine oil Liquid
1.2	Identified uses Distribution of substance Formulation & (re)packing of substances and mixtures Manufacture of substance Functional Fluids	Industrial Industrial Industrial Industrial
1.3	Details of the supplier of the safet	y data sheet
	Supplier/Manufacturer	APAR Industries Limited 18 T.T.C., M.I.D.C. Industrial Area , Thane Belapur Road , Rabale, Navi Mumbai – 400701. India. +91 22 61110444 (Office hours 9.30am to 17.00pm) www.apar.com
14	e-mail address of person responsible for this SDS Emorgoney tolerabore pumber	hse@apar.com +91 9833811132
1.4	Emergency telephone number	+717033011132

SECTION 2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture Mixture

Product definition

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Asp. Tox. 1, H304

Signal word

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

2.2 Label elements

Hazard pictograms



Danger

11 204 r r ш

Hazard statements	H 304 : May be tatal it swallowed and enters airways.
Precautionary statements	Not applicable
Prevention	P301 + P310 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce
Response	vomiting.
Storage	P405 - Store locked up.
Disposal	P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable

2.3 Other hazards

Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Not applicable

Not applicable



Safety Data Sheet Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

SECTION 3 COMPOSTION/ INFORMATION ON INGREDIENTS

3.2 Mixtures	Mixture			
Product/Ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Туре
Distillate (petroleum), hydro treated Heavy Paraffinic,	CAS: 64742-54-7	80 - 90	Asp. Tox. 1, H304	[1]
Zinc dialkyl Dithiophosphate Alkaryl amine (Additive) Organomolybdenum amide	(CAS No) 68649-42-3 Proprietary	1-2,4	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 4, H413 Aquatic Chronic 2, H411 Aquatic Chronic 2, H411	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

SECTION 4 FIRST AID MEASURES

4.1 Description of first aid measures

4.1 Description of mar did medadres	
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
	rinsing. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist.
	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If casualty is unconscious and: If not breathing, if breathing is irregular or if respiratory arrest occurs, provide
Inhalation	artificial respiration or oxygen by trained personnel. Get medical attention if adverse health effects persist
	or are severe. Maintain an open airway.
	Wash with soap and water. Remove contaminated clothing and shoes. Handle with care and dispose of in a
Skin contact	safe manner. Seek medical attention if skin irritation, swelling or redness develops and persists.
	Accidental high pressure injection through the skin requires immediate medical attention. Do not wait for symptoms to develop.
	Always assume that aspiration has occurred. Do not induce vomiting. Can enter lungs and cause damage. If
Ingestion	vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Seek professional medical attention or send the casualty to a hospital. Do not wait for symptoms to develop.
ingesion	Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get
	medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the
	person providing aid to give mouth-to-mouth resuscitation.
	Before attempting to rescue casualties, isolate area from all potential sources of ignition including
Protection of first-aiders	disconnecting electrical supply. Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects		
Eye contact	Eye contact may cause redness and transient pain.	
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.	
Skin contact	No known significant effects or critical hazards.	
Ingestion	May be fatal if swallowed and enters airways.	
4.3 Indication of any immediate med	lical attention and special treatment needed	
Notes to physician	Due to low viscosity there is a risk of aspiration if the product enters the lungs. Treat symptomatically.	
Specific treatments	Always assume that aspiration has occurred.	



SECTION 5 FIRE FIGHTING MEASURES				
5.1 Extinguishing media				
Suitable extinguishing media Unsuitable extinguishing media	Dry chemicals. Foam. Carbon dioxide (CO ₂). Water spray or foam. Do not use direct water jets on the burning product; they could cause splattering and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.			
5.2 Special hazards arising from the	substance or mixture			
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst. This substance will float and can be reignited on surface water.			
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H2S, SOx (sulfur oxides) or sulfuric acid and unidentified organic and inorganic compounds.			
5.3 Advice for firefighters				
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.			
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.			
SECTION 6 ACCIDENTAL RELEASE	E MEASURES			
	equipment and emergency procedures			
For non-emergency personnel	Avoid breathing vapour or mist. Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind/keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed ,are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions.			
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note : gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.			
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.			



Safety Data Sheet Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

6.3 Methods and material for contair	nment		
and cleaning up			
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.		
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.		
6.4 Reference to other sections		for emergency contact information.	
		for information on appropriate personal protective equipment. 3 for additional waste treatment information.	
SECTION 7 HANDLING AND STO	RAGE		
7.1 Advice on general occupational		oper housekeeping measures are in place. Contaminated materials should not be allowed to	
hygiene Storage	should be pr thoroughly afte	the workplaces and should never be kept inside the pockets. Eating, drinking and smoking ohibited in areas where this material is handled, stored and processed. Wash hands er handling. Change contaminated clothes at the end of working shift. See also Section 8 for rmation on hygiene measures.	
7.2 Conditions for safe storage,	-	layout, tank design, equipment and operating procedures must comply with the relevant	
including any incompatibilities	•	nal or local legislation. Storage installations should be designed with adequate bunds in case	
including any incompany incompany	ncluding any incompatibilities of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.		
SECTION 7 HANDLING AND STO	RAGE		
7.2 Conditions for safe storage,	•	ly from oxidising agents.	
including any incompatibilities Recommended materials for containers, or container linings use mild steel, stainless steel. Not suitable Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Compatibility should be checked with the manufacturer. Keep only in the original container or in a suitable container for this kind of product. Keep container tight closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have bee opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable/combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse of dispose of containers unless adequate precautions are taken against these hazards. Store locked up. Protect from sunlight.			
7.3 Specific end use(s)	Not available Not available		
Recommendations	INOT AVAILABLE		
Industrial sector specific solutions			
SECTION 8 EXPOSURE CONTRO	LS / PERSON	VAL PROTECTION	
The list of Identified Uses in Section 1 should	be consulted for	any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters			
Occupational exposure limits			
Product/Ingredient name		Exposure limits values	
Distillate (petroleum), hydro treated Hea	vy	PEL 5 mg/m3 Mist.	
Naphthenic			
Naphthenic			



	Commission Regulation (EU) 2015/830.
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance
	documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure Control Appropriate engineering	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Controls	
<u>Individual protection measures</u> Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse. Recommended: Safety glasses with side shields.
Eye/face protection	
Skin protection	4 - 8 hours (breakthrough time): nitrile rubber
Hand protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of
Body protection	working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
	Emissions from ventilation or work process equipment should be checked to ensure they comply with the
Environmental exposure controls	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering
	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
SECTION 9 PHYSICAL AND CH	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering
	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES
SECTION 9 PHYSICAL AND CH Appearance	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear
SECTION 9 PHYSICAL AND CH Appearance Physical state	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold pH	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor Odor threshold pH Melting point/Pour point	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97)
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor Odor threshold pH Melting point/Pour point Flash point	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C ,COC (ASTM D 92)
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C ,COC (ASTM D 92) Not available
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas)	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C , COC (ASTM D 92) Not available Not available
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability limits in air,	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C ,COC (ASTM D 92) Not available
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas)	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C , COC (ASTM D 92) Not available Not available
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability limits in air, lower, % by volume Flammability limits in air,	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C ,COC (ASTM D 92) Not available Not available Not available Not available Not available
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability limits in air, lower, % by volume Flammability limits in air, upper, % by volume	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C ,COC (ASTM D 92) Not available Not available Not available Not available Not available
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability limits in air, lower, % by volume Flammability limits in air, upper, % by volume Vapour pressure Density Solubility(ies)	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. EEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C ,COC (ASTM D 92) Not available Not available Not available Not available Not available Not available Not available Soft available Not available
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability limits in air, lower, % by volume Flammability limits in air, upper, % by volume Vapour pressure Density Solubility (ies) Solubility (water)	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. EEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C ,COC (ASTM D 92) Not available Not available Not available Not available Not available Not available Sol, 1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010 0.880 max at 15°C Insoluble in water
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability limits in air, lower, % by volume Flammability limits in air, upper, % by volume Vapour pressure Density Solubility (ies) Solubility (water) Partition coefficient	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. EEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C ,COC (ASTM D 92) Not available Not available Not available Not available Not available Not available Not available Soft available Not available
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability (solid, gas) Flammability limits in air, lower, % by volume Flammability limits in air, upper, % by volume Flammability limits in air, upper, % by volume Vapour pressure Density Solubility(ies) Solubility (water) Partition coefficient (n-octanol/water)	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. EMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C, COC (ASTM D 92) Not available Not available Not available Not available Not available Soft available
SECTION 9 PHYSICAL AND CH Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability (solid, gas) Flammability limits in air, lower, % by volume Flammability limits in air, upper, % by volume Vapour pressure Density Solubility (ies) Solubility (water) Partition coefficient (n-octanol/water) Decomposition temperature	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. EMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C, COC (ASTM D 92) Not available Not available Not available Not available So 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010 0.880 max at 15°C Insoluble in water Not available No Data
SECTION 9 PHYSICAL AND CF Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability (solid, gas) Flammability limits in air, lower, % by volume Flammability limits in air, upper, % by volume Vapour pressure Density Solubility (ies) Solubility (water) Partition coefficient (n-octanol/water) Decomposition temperature Auto-ignition temperature	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. EMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not applicable < -27°C (ASTM D-97) > 200°C , COC (ASTM D 92) Not available Not available Not available Not available Not available S 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010 0.880 max at 15°C Insoluble in water Not available No Data > 300°C
SECTION 9 PHYSICAL AND CF Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability limits in air, lower, % by volume Flammability limits in air, upper, % by volume Vapour pressure Density Solubility (ies) Solubility (water) Partition coefficient (n-octanol/water) Decomposition temperature Auto-ignition temperature Viscosity, Kinematic at 40°C (104°F)	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not available $< 2.7^{\circ}C$ (ASTM D-97) $> 200^{\circ}C$, COC (ASTM D 92) Not available Not available
SECTION 9 PHYSICAL AND CF Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability limits in air, lower, % by volume Flammability limits in air, upper, % by volume Vapour pressure Density Solubility(ies) Solubility (water) Partition coefficient (n-octanol/water) Decomposition temperature Auto-ignition temperature Viscosity, Kinematic at 40°C (104°F) Explosive properties	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not available Not available Not available Not available Not available Not available Not available Not available Soluble in water Not available No Data > 300°C 11.0 mm ² /s 100 °C) (ASTM D445) No Data
SECTION 9 PHYSICAL AND CF Appearance Physical state Color Odor Odor threshold pH Melting point/Pour point Flash point Evaporation rate Flammability (solid, gas) Flammability limits in air, lower, % by volume Flammability limits in air, upper, % by volume Vapour pressure Density Solubility (ies) Solubility (water) Partition coefficient (n-octanol/water) Decomposition temperature Auto-ignition temperature Viscosity, Kinematic at 40°C (104°F)	requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. IEMICAL PROPERTIES Clear Liquid Yellow to Brown Motor oil odor Not available Not available $< 2.7^{\circ}C$ (ASTM D-97) $> 200^{\circ}C$, COC (ASTM D 92) Not available Not available





Safety Data Sheet Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
Reactions	Keep away from extreme heat and oxidizing agents.
10.4 Conditions to avoid	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates,
10.5 Incompatible materials	gases, including carbon monoxide, H2S, SOx (sulfur oxides) or sulfuric acid and unidentified organic and
10.6 Hazardous decomposition	inorganic compounds.
products	

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
Distillate (petroleum), hydro treated Heavy	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours
paraffinic	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 fish 1	Fish 1	4,4 mg/l	96 hours
Zinc dialkyl Dithiophosphate	EC50 Daphnia 1	Daphnia 1	5,4 mg/kg	48 hours
Alkaryl amine (Additive)	LD 50 Dermal	Rabbit	>2000mg/kg	-
Organomolybdenum	LD 50 Oral	Rat	>5000 mg/kg	-
amide	LD 50 Oral	Rat		
Irritation/Corrosion				
Skin	No known significant effects or critical h			
Eye	No known significant effects or critical h			
Respiratory	No known significant effects or critical h	nazards.		
<u>Sensitisation</u> Skin	No known aignifig-ut affa-ta an a triad	anarda		
Skin Respiratory	No known significant effects or critical l No known significant effects or critical l			
Mutagenicity	-		ont at greater than 0.1%	aro mutagonic or
Mulagemeny	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
SECTION 11 TOXICOLOGICAL IN	*			
Carcinogenicity	The base oil(s) in this product is based	d on an severely hydr	otreated distillate. The p	product should not
	regarded as a carcinogen.			
Reproductive toxicity	Contains no ingredient listed as toxic to	reproduction.		
Specific target organ toxicity	Not classified			
- single exposure				
Specific target organ toxicity	Not classified			
- repeated exposure				
Aspiration hazard	Aspiration hazard - Category 1			
Information on likely routes of exposure	Not available.			
Potential acute health effects				
		sight pain		
Eye contact	Eye contact may cause redness and tran	•		
Inhalation	Inhalation of oil mist or vapours at eleva		cause respiratory irritation	on.
Skin contact	No known significant effects or critical h			
Ingestion	May be fatal if swallowed and enters air	ways.		
Potential chronic health effects				
General	No known significant effects or critical l	nazards.		
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be			
	regarded as a carcinogen.			
Mutagenicity	No known significant effects or critical h	nazards		



Safety Data Sheet Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

Teratogenicity	No known significant effects or critical hazards.
Product/ingredient name	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Other information	Not available.
Specific hazard	
SECTION 12 ECOLOGICAL INFO	RMATION
12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB Assessment	Not applicable.
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

SECTION 13 DISPOSAL CONSIDERATIONS

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Yes

13.1 Waste treatment methods

- <u>Product</u>
- Methods of disposal

Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorizations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organization, and/or prescribe composition limits and methods for recovery or disposal.

Hazardous waste

SECTION 13 DISPOSAL CONSIDERATIONS

European waste catalogue (EWC)

<u>Luiopean wasie calalogue (Livic)</u>	
Waste code	Waste designation
13 03 07*	mineral-based non-chlorinated insulating and heat transmission oils
Packaging	
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be
	recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14 TRANSPORT INFORMATION

International transport regulations

	ADR/ RID	ADN	IMO/IMDG Classification	ICAO/IATA Classification
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No	No	No	No
Additional information	-	-	-	-



Safety Data Sheet Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure

that persons transporting the product know what to do in the event of an accident or spillage.

14.6 Special precautions for User

14.7 Transport in bulk according to Annex I of MARPOL

APAR Industries Limited

73/78 and the IBC Code

SECTION 15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization Annex XIV None of the components are listed. None of the components are listed. Substances of very high concern Annex XVII - Restrictions on the Not applicable. manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Other EU regulations Seveso D This product is not controlled under the Seveso Directive. International Lists Inventory name On inventory (yes/no)* National Inventory

Australia	Australian Inventory of Chemical Substances (AICS)	
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	
Korea	Existing Chemicals List (ECL)	
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory		Yes
at the second		

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

15.2 Chemical Safety Assessment

SECTION 16 OTHER INFORMATION				
Revision comments	Not available.			
Legend to abbreviations				
ADR	European agreement concerning the international carriage of dangerous good by road.			
RID	Regulations agreement concerning the international carriage of dangerous good by rail.			
IMDG – CODE	International maritime dangerous goods code.			
ICAO	International Civil Aviation Organization.			
IATA	International air transport association.			
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.			
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].			
SCBA	Self-Contained Breathing Apparatus.			
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC)			
	No. 1907/2006].			
LC 50	Median lethal concentration.			
LD 50	Median lethal dose.			
PBT	Persistent, Bioaccumulative and Toxic.			
Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]				

Classification	Justification
Asp. Tox. 1, H304	Calculation method



1st October 2020. January 2019

02

H304 May be fatal if swallowed and enters airways.

Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1.

Safety Data Sheet Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

Full text of abbreviated H statements Full text of classifications [CLP/GHS] Date of issue/Date of revision Date of previous issue Version

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.