

PREMIUM MULTI 15W 40

PREMIUM MULTI SAE 15W 40 is a high performance Heavy Duty Diesel Engine oil for all turbo charged diesel engines of HCV,LCV,DG SETS or Off Road equipments. It has very high oxidation and thermal stability and stays in the right viscosity grade to provide optimum lubrication to important engine parts. It keeps the engine clean from any deposits and protects it from corrosion. Its flows very fast to turbo charger at times of cranking to avoid dry running of turbo charger bearing and protects it from wear.

Advantages:-

- Keeps the engine clean and prolongs the engine's life.
- Protects the turbo charger from wear during starting of the engine when there is no lubricant present in the turbocharger. Its high fluidity makes the oil reach fast to turbo charger to protect it at high RPM.
- It can be used in engine complying with EURO II norms.

Typical Characteristics:-

PREMIUM MULTI 15W 40		
TEST PARAMETERS	METHOD	TYPICAL VALUES
Density @29.5°C. gm/cc	ASTMD 1298	0.862
Kin.Viscosity @40°C, cSt	ASTM D 445	105.8
Kin.Viscosity @100°C, cSt	ASTM D 445	13.9
Viscosity Index	ASTM D 2270	132
Flash Point, °C	ASTM D 92	226
Pour Point, °C	ASTM D 97	-24
TBN, mgKOH/gm	ASTM D2896	9.5
CCS @-20°C ,cp	ASTM 5293	6200

Product Performance Claims:-

It meets and exceeds API CH-4/CF 4/CF/CD, MAN 3275, MB 228.3, VDS-2 performance specification.

APAR Industries Limited

Corporate Office: APAR House, Corporate Park, V N Purav Marg, Chembur, Mumbai 400 071, India
+91 22 2526 3400 / 6780 0400 corporate@apar.com www.apar.com

Regd Office: 301 / 306, Panorama Complex, RC Dutt Road, Vadodara 390 007, India
+91 265 2323 175 / 2323 176 corporate@apar.com www.apar.com CIN: L91110GJ1989PLC012802