

CRUISE MULTI 20W 50

CRUISE MULTI 20W 50 is latest car engine oil for MPFI, Common Rail, Turbo or Multi Jet engines. It provides all round protection for your car engines from wear and corrosion. It can be used in any types of Petrol, Diesel or CNG/LPG cars. It keeps the engine clean from high temperature deposits and sludge

Advantages:-

CRUISE MULTI 20W-50

- Contains anti-sludge properties that provides better sludge protection.
- Superior protection against viscosity and thermal breakdown
- Anti-wear additives that extend the life of your engine.

Application:-

CRUISE MULTI 20W-50 is suitable for use in automotive petro and gas engines where the manufacturer recommends an API SL or earlier specification 20W-50 lubricant. For diesel engines API CF or CD grades.

CRUISE MULTI 20W 50		
TEST PARAMETERS	METHOD	TYPICAL VALUES
Density @29.5°C. gm/cc	ASTMD 1298	0.883
Kin. Viscosity @40°C, cst	ASTM D 445	161.65
Kin. Viscosity @100°C, cst	ASTM D 445	17.5
Viscosity Index	ASTM D 2270	118
Flash Point, °C	ASTM D 92	228
Pour Point, °C	ASTM D 97	-21
TBN, mgKOH/gm	ASTM D2896	7.4
CCS @-15°C , cp	ASTM 5293	7700

Typical Characteristics:-

Product Performance Claims:

API SL/ CF, SJ/SG/SF.

APAR Industries Limited

Corporate Office: APAR House, Corporate Park, V N Purav Marg, Chembur, Mumbai 400 071, India +91 22 2526 3400 / 6780 0400 corporate@apar.com

Regd Office: 301 / 306, Panorama Complex, RC Dutt Road, Vadodara 390 007, India +91 265 2323 175 / 2323 176 corporate@apar.com <u>www.apar.com</u> CIN: L91110GJ1989PLC012802