

PREMIUM 15W40 CF4

POWEROIL PREMIUM 15W40 CF4 is a commercial multipurpose diesel engine oil meeting the requirements of off-highway diesel engines and DG sets operating on distillate fuels. Also recommended for petrol engines, enabling effective usage in mixed fleet operations. It provides very good protection against high temperature engine deposits, oil degradation, oil thickening, rust and corrosion. It has excellent shear stability and maintains viscosity even under severe, high temperature operations.

PERFORMANCE STANDARDS:

API CF4/SF

VW 505 issue 11/92

Daimler Benz 228.1

MAN 271

CCMC D4 and PD-2

Mack EO-K2

 IS 13656: 2014 (2nd Revn.), EDL-5

CHARACTERISTICS	POWEROIL ENGINE CF4
	15W40
Kinematic Viscosity, @ 100°C, cSt	14.5
Viscosity index, Min.	130
Flash point (PMCC), °C., Min.	200
Pour point, °C., Max.	-24
TBN, mg KOH/gm	7.0

The above properties are typical values and do not constitute specification of the product

APPLICATION:

- Recommended for use in modern diesel engines. Also suitable for petrol engines.

PERFORMANCE BENEFITS:

- Ease in cold starting due to very high viscosity index Maintains high order of engine cleanliness
- Very good protection against high temperature engine deposits, oil degradation, oil thickening, rusting and corrosion.