

POWEROIL TOPAZ L 110

Meets the requirements of US FDA 21 CFR 178.3620 (b).

Sr No	Characteristics	Unit	Test Method	Specification	
				Min.	Max.
1	Appearance	-	Visual	Transparent, colourless, bright and clear oily liquid.	
2	Color, Saybolt	-	ASTM D 156	+25	-
3	Density at 25°C	gm/ml	ASTM D 1298	0.820	0.860
4	Kinematic Viscosity at 40°C	cSt	ASTM D 445 / D 7042	21.00	24.00
5	Flash Point, (COC)	° C	ASTM D 92	170	-
6	Pour Point	° C	ASTM D 97	-	-12

POWEROIL TOPAZ L 110 (TECHNICAL GRADE WHITE OIL) is a light white oil formulated from highly refined hydrotreated base oils which is colorless, tasteless and odorless.

It meets US FDA 21 CFR 178.3620 (b) requirements for (+25) Saybolt color & UV absorbance.

Application: **POWEROIL TOPAZ L 110** is suitable for use in processes/products requiring clear white oils. These oils find extensive usage in textile processing (non staining lubrication) , incense & perfume manufacture, plastic, paper and cosmetic industries, several oil based formulations, hair oils, hair lotions, shoe polish and petroleum jelly manufacturing industries.

Performance Benefits : Excellent oxidation resistance

High film strength

Non staining