

POWEROIL TO 20 BS

POWEROIL TO 20 BS is an Uninhibited Transformer Oil meeting BS 148 Class I: 1984 Standard Specification.

Sr No	Characteristics	Unit	Test Method	Guaranteed Data	
				Min	Max
1	Appearance		Visual inspection of oil sample in transmitted light under a thickness of 10 cm at ambient temperature	Clear free from sediment and suspended matter	
2	Density at 20 ° C	g /ml	BS 4714		0.895
3	Kinematic Viscosity at 40 ° C	mm ² / sec	BS 2000 Part 71		16.5
	at - 15 ° C				800
4	Flash Point, PMCC	° C	BS 2000 Part 34	140	
5	Pour Point	° C	BS 2000 Part 15		- 30
7	Neutralization value	mg KOH/ g	BS 2000 Part 1		0.03
8	Water Content, Bulk/ Drum, IBC	mg / kg	BS 6470		30 / 40
9	Breakdown Voltage		BS 5874		
	As Delivered	kV		30	
10	Dielectric Dissipation Factor (Tan δ) at 90 ° C & 40 to 60 Hz		BS 573		0.005
11	Corrosive Sulphur Copper Strip, 140 ° C, 19 Hrs.		BS 5680 : 1979	Non Corrosive	
12	Anti-Oxidant additives	%	BS 5984 : 1980	Not Detectable	
13	Oxidation Stability at 120 ° C, 164 Hrs.		BS 148 : 1984 Appendix A		
	Total Acidity	mg KOH /g			1.5
	Sludge	%			1.0
14	Gassing Tendency at 50 Hz after 120 minutes	mm ³ / min	BS 5797 Method A		+ 5