

POWEROIL TRANSMISSION C4 FLUID TRANSMISSION FLUIDS

POWEROIL TRANSMISSION C4 FLUIDS are formulated from highly refined base oils and high performance additive package which enable good lubrication and anti-wear properties. They provide low co-efficient of friction in line with specific equipment manufacturers' requirements.

PERFORMANCE STANDARDS:

Meet TES 228 of Allison Division of G.M., U.S.A
Allison C 4, EDL-3 of IS 13656:2014

CHARACTERISTICS	POWEROIL TRANSMISSION C4 FLUID		
	10W	30	40
SAE	10W	30	40
Colour	Red	Red	Red
Kinematic viscosity @ 100°C cSt	7.0	10.5	14.8
Viscosity Index, Min.	100	100	95
Flash point, °C (COC), Min.	180	200	215
Pour Point, °C., Max.	-30	-18	-12
TBN mg KOH/g	7	7	7

The above properties are typical values and do not constitute specification of the product

APPLICATION:

- POWEROIL TRANSMISSION C4 is recommended as a service Lubricant for on highway and off highway equipment's addressing Allison Heavy Duty Transmission requirements.

PERFORMANCE BENEFITS:

- Excellent oxidation stability and hence longer oil life.
- Meets superior non- asbestos clutch friction test.
- Good anti-foam & anti-rust properties.