

POWEROIL GEAR EP 85W 140 EXTREME PRESSURE GEAR OIL

POWEROIL GEAR EP 85W 140 oil is an extreme pressure multipurpose multigrade gear oil formulated from highly refined high viscosity index base stocks and select additives.

MEETS THE FOLLOWING PERFORMANCE STANDARDS:

BIS : 1118 -1992 (reaffirm 2016), EP Type, GL-5

API Service Classification GL-5 Level

U.S. Military MIL - L - 2105 D

CHARACTERISTICS	POWEROIL GEAR EP
SAE No	85W 140
Kinematic Viscosity @ 100°C, cSt	29.5
Viscosity index, min	95
Pour Point, oC., Max.	-12
Flash point, COC, oC, min.	190

The above properties are typical values and do not constitute specification of the product

APPLICATION:

- Recommended for use in gearboxes and rear axles where extreme pressure properties are required particularly for hypoid and bevel gears. Also recommended for vehicles operating in low temperature areas.
- Not recommended for industrial gears having copper or copper alloy parts.

PERFORMANCE BENEFITS:

- Multipurpose Lubricant
- Excellent Extreme pressure properties thereby leading to long gear life.
- Outstanding anti-rust characteristics leading to rust and corrosion prevention.
- Excellent anti-foam properties.