POWEROIL HTCO
HIGH TEMPERATURE CHAIN OIL

POWEROIL HTCO is blended with synthetic base stocks and high performance additive packages to meet high temperature and trouble free performance requirements of chain conveyor systems used in textile, food beverages, automotive and pharmaceutical industries.

CHARACTERISTICS	POWEROIL HTCO
Appearance	Clear Liquid
Kinematic viscosity@ 40°C, cSt	210 - 230
Flash Point, °C (COC)Min.	>250
Copper strip corrosion test	1a
Conradson carbon residue, % by weight	<0.1

The above properties are typical values and do not constitute specification of the product

APPLICATION:

- Power Oil HTCO can be applied by spray, drip or by brushing for the lubrication of chains, conveyors in normal to high temperature applications up to 250 °C, such as Stenter machines etc.

PERFORMANCE BENEFITS:

- Low deposits on chains at high temperatures.
- Outstanding adhesive properties;
- Low evaporation loss
- High oxidation stability;
- Excellent anti-wear properties ensuring trouble free and long life of chains;
- Excellent antirust properties;
- Extended re-lubrication intervals.

Disclaimer: APAR makes no warrantees, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility. Website: www.apar.com