

## POWEROIL PRESS PREMIUM COMPRESSOR OIL

**POWEROIL PRESS** oils are best in class mineral oil based air compressor oils designed to meet the stringent performance requirements of compressor manufacturers. They are formulated from high quality carefully chosen highly refined base stocks with superior performance additive package to deliver top of the line performance coupled with excellent equipment protection.

**MEET THE PERFORMANCE STANDARDS OF:** ISO DIS-6521, DIN 51506VDL, BIS – 13256-1992 (Reaffirmed 2014)

CHARACTERISTICS	POWEROIL Press			
	68	100	150	220
ISO VG	68	100	150	220
Colour	2.5	3.5	4.0	5.0
Kinematic Viscosity @ 40°C, cSt	68	100	150	220
Viscosity index, Min.	95	95	95	90
Flash point, COC, °C, Min.	210	216	220	230
Pour point, °C, Max.	-9	-6	-6	-6
CCR % Wt.	0.05	0.05	0.15	0.40
Rust test D-665 (A&B) 24 hrs	Pass	Pass	Pass	Pass

The above properties are typical values and do not constitute specification of the product

### APPLICATION:

- Recommended for lubrication of severe duty reciprocating and rotary air compressors with air discharge temperature up to 220 °C.
- Suitable for lubrication of most types of OEM equipment's as product is designed to meet OEM performance levels.

### PERFORMANCE BENEFITS:

- Good lubrication even under high operating temperatures and high load conditions.
- Excellent corrosion and rust protection characteristics
- Excellent anti wear properties offering enhanced equipment life
- Reduced fire and explosion risks due to low volatility and high auto ignition temperature.
- Low carbon and deposit forming characteristics.