

## POWEROIL WAYLUBE SUPERIOR MACHINE TOOL WAY OILS

**POWEROIL WAYLUBE** oils are superior performance machine tool way lubricants formulated from highly refined base stocks and fortified with anti-rust, tackiness and mild EP additives

**PERFORMANCE STANDARDS:** ASLE standard W 315 and W 1000  
Cincinnati Milacron specifications, P- 47 and P- 50

CHARACTERISTICS	POWEROIL WAYLUBE	
	68	220
ISO VG	68	220
Kinematic Viscosity @ 40°C, cSt	67	220
Flash point, COC, °C., Min.	200	220
Pour point, °C., Max.	-6	-3
Rust test (D-665A, 24 hrs)	Pass	Pass

The above properties are typical values and do not constitute specification of the product

### APPLICATION:

- Recommended for slideway lubrication of grinders, planers, shapers, horizontal boring machines, knitting machines, jig bores, etc. involving high precision work.
- Also suitable for slideway lubrication of modern CNC, VMC, HMC and Convectional machines

### PERFORMANCE BENEFITS:

- Excellent lubrication characteristics
- Minimize stick-slip and chatter, thereby giving improved surface finish to the job
- Reduced oil consumption, due to good adhesive characteristics of the oil
- Provide protection from rust and corrosion
- Suitable for higher loading of machine tools