POWEROIL DRFM LIGHT PREMIUM

POWEROIL DRFM LIGHT PREMIUM is an environment-friendly de-aromatized hydrocarbon product with water white color, low odor and extremely low aromatic content.

CHARACTERISTICS	POWEROIL DRFM LIGHT PREMIUM
Colour	0.5
Specific Gravity,	0.795
Kinematic viscosity @ 40oC, cSt	1.8
Distillation Range	
Initial Boiling Point in °C	210
End Point	250
Flash point ,COC, °C	80
Sulfur Content, ppm	Nil
Aromatic Content	Nil

The above properties are typical values and do not constitute specification of the product

APPLICATION:

- Recommended for Aluminum sheet rolling as well as various metal working applications.
- Also suitable for air heat exchanger aluminum fin stamping Application.

PERFORMANCE BENEFITS:

- Good lubrication even under extended high load condition
- Excellent drying properties post stamping.
- High flash point, hence less volatile and safe to handle and use.

STORAGE & HANDLING:

- Keep in cool, dry, ventilated condition and in closed containers.
- Keep away from heat sources and direct sunlight.
- Recommended safe handling procedures are discussed in the SDS.
- Review and understand the implications before commencing operations

Disclaimer: APAR makes no warrantees, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility. Website: www.apar.com