



POWEROIL HONE 7S CHLORINE FREE HONING OIL

POWEROIL HONE 7S is a low viscosity Honing & Grinding oil free of chlorine. It is a blend of select base oil fortified with exclusive lubricity & EP additives that impart excellent surface finish to hardened steels and nickel alloys.

| CHARACTERISTICS | POWEROIL HONE 7S | |
|---------------------------------|--------------------|--|
| Appearance | Clear Amber Liquid | |
| Kinematic Viscosity @ 40°C, cSt | 5.0 | |
| Copper corrosion 100 C 3 Hrs | 1b | |
| Density @ 20°C,gm/cc | 0.830 | |
| Flash point, °C (PMCC), Min. | 120 | |

The above properties are typical values and do not constitute specification of the product

APPLICATION:

- Recommended for honing / micro finishing of both Ferrous & Non Ferrous metals to achieve Superior surface finish
- Can be used for honing operation of toughened steels e.g. bearing steels and nickel alloys etc.
- Also applicable for grinding application.
- Suitable for light drawing and forming applications.

| | Cast Iron | Low Medium Alloy Steel | High Alloy Steel/ Nickel Chromium Alloy | Aluminium Alloy | Yellow Metal |
|------------------------|--------------|---------------------------|-----------------------------------------------|--------------------|-----------------|
| Honing/Super finishing | ✓ | ✓ | ✓ | ✓ | ✓ |
| Grinding | ✓ | ✓ | ✓ | ✓ | ✓ |
| Drilling | | | | | |
| General Machining | | | | ✓ | √ |

PERFORMANCE BENEFITS:

- Offers best in class surface finish to machined/honed components
- Chlorine-free product resulting in lower used oil disposal cost
- Excellent inherent oxidation resistance characteristics